

## Contact Details

Contact us if you require more detail about this product or would like to arrange a demonstration unit for your network.

**Web:**

[www.blio.com](http://www.blio.com)

**Tel:** +27 21 689 3878

**Physical Address:**

Cape Town Office:

1st Floor

Albion Springs Building

183 Main Road

Newlands

Cape Town

South Africa

Stellenbosch Office:

Innovation Centre No.1, Unit 5

Meson Street

Technopark

Stellenbosch

South Africa

**Postal Address:**

P.O. Box 23618

Claremont

Western Cape

South Africa

7735

**blio corporation**  
pragmatic information infrastructure

VX 1600 Series  
IP PBX



## VX 1600 Series IP PBX

Introducing the first **South African** designed and manufactured, affordable **IP** and **Analog** converged **PBX**, that's rack mountable, stackable (so it grows with your needs) and easy to configure with a web interface.



## Product Overview

### External Connectivity:

- 2 ISDN ports, 4 channels
- 2 Analog Trunk ports, GSM-LCR (FXO)
- 1 VoIP Trunk (SIP Provider)

### Internal Connectivity:

- 10 Analog Extension ports for standard desk phones (FXS)
- 20 SIP extensions for VoIP phones (10 GSM Codec concurrent calls)
- 1 10/100 Ethernet port

### Feature Summary:

- Stackable
- Low power, No moving parts
- 1U, Rackmount or Wallmount Casing
- Designed and manufactured in **Cape Town, ZA**
- User friendly web interface for management
- 12 Month Warranty with Free Software Updates

## Web Management Interface



Device Status Overview page

Add / Remove page

## Company Overview

The **Blio Corporation** designs infrastructure for the next generation converged public network. We build innovative platforms for voice and data service delivery with a focus on manageability. Blio helps you deploy cost effective, scalable and dependable networks.

Visit [www.blio.com](http://www.blio.com) for more detail.

## Telephony Features

- Incoming call routing based on **MSN** number
  - Incoming call answer groups with configurable timers
  - Multiple answer groups and/or Operator
  - Hold, Divert, Conference, Transfer, Call pick-up
- 
- Configurable numbering scheme
  - Call logging (display, or export to spread-sheet)
  - Interactive Voicemail
  - Voicemail to email with attached .wav files
  - Speed-dial numbers (abbreviated dialing)
- 
- Virtual PBXs (tenant) functionality
  - Least-cost routing based on number dialed
  - Factory reset via simple push-button and LEDs on the front panel

## Specifications

- **Dimensions** 438 mm x 362 mm x 44.45 mm (1U)
- **Power Consumption** 40 Watts (idle)
- **Weight** 4Kg

## Installation Options

